




## Катушка индуктивности цепи ВЧ-коррекции PEAKING COILS

### Specifications

1. Inductance
2. Operating Frequency

|  |                             | DIMENSIONS (mm)   |   |   |
|--|-----------------------------|---|---|---|
|  | Power supply, T.V. recorder | -5 different sizes<br>-Ferrite and phenolic core are available<br>-Axial type leads | 1. 1 $\mu$ H~1000 $\mu$ H<br>2. 100kHz~200MHz |   |
|  |                             |   |   |  |

### SPECIFICATION TABLE

|      | Dimensions (mm) |            |               |     |     | TABLE |
|------|-----------------|------------|---------------|-----|-----|-------|
|      |                 |            |               |     |     |       |
| CWRR | 29 $\pm$ 1      | 29 $\pm$ 1 | 9.4 $\pm$ 0.3 | 0.6 | 3.1 | -     |
|      |                 |            |               |     |     | -     |
| CWR5 | 21 $\pm$ 1      | 21 $\pm$ 1 | 20 $\pm$ 1.0  | 0.6 | 5   | P.115 |
|      |                 |            |               |     |     | P.116 |
| CWR6 | 38 $\pm$ 1      | 38 $\pm$ 1 | 30 $\pm$ 1.0  | 0.6 | 6   | P.116 |

### Specification table of Peaking Coils CWR5

|           |      |       |       | SRF MHz (Min.) |
|-----------|------|-------|-------|----------------|
| CWR5-1R0M | 1.0  | 0.011 | 3.0   | 170            |
|           |      |       |       | 144            |
| CWR5-2R2M | 2.2  | 0.013 | 3.0   | 122            |
|           |      |       |       | 120            |
| CWR5-4R7M | 4.7  | 0.017 | 3.0   | 97             |
|           |      |       |       | 88             |
| CWR5-100K | 10   | 0.029 | 3.0   | 81             |
|           |      |       |       | 68             |
| CWR5-220K | 22   | 0.088 | 3.0   | 62             |
|           |      |       |       | 8.5            |
| CWR5-470K | 47   | 0.090 | 2.5   | 4.4            |
|           |      |       |       | 2.95           |
| CWR5-101K | 100  | 0.180 | 1.9   | 2.75           |
|           |      |       |       | 2.05           |
| CWR5-221K | 220  | 0.268 | 1.13  | 1.8            |
|           |      |       |       | 1.6            |
| CWR5-471K | 470  | 0.487 | 0.645 | 1.3            |
|           |      |       |       | 1.2            |
| CWR5-102K | 1000 | 0.954 | 0.127 | 1.0            |

※ Specifications other than the above will be furnished upon request.



# PEAKING COILS

**Specification table of Peaking Coils CWR6**

|           |      |       |       | SRF MHz (Min.) |
|-----------|------|-------|-------|----------------|
| CWR6-1R0M | 1.0  | 0.013 | 3.5   | 102            |
|           |      |       |       | 102            |
| CWR6-2R2M | 2.2  | 0.016 | 3.5   | 102            |
|           |      |       |       | 95             |
| CWR6-4R7M | 4.7  | 0.023 | 3.5   | 79             |
|           |      |       |       | 70             |
| CWR6-100K | 10   | 0.036 | 3.5   | 61             |
|           |      |       |       | 56             |
| CWR6-220K | 22   | 0.073 | 3.5   | 44             |
|           |      |       |       | 9.9            |
| CWR6-470K | 47   | 0.113 | 3.5   | 4.5            |
|           |      |       |       | 3.7            |
| CWR6-101K | 100  | 0.126 | 3.0   | 2.8            |
|           |      |       |       | 1.9            |
| CWR6-221K | 220  | 0.326 | 1.5   | 1.6            |
|           |      |       |       | 1.45           |
| CWR6-471K | 470  | 0.504 | 0.83  | 1.33           |
|           |      |       |       | 1.03           |
| CWR6-102K | 1000 | 1.000 | 0.135 | 0.92           |

**Specification table of Peaking Coils CWR6**

|           |      |       |      | SRF MHz (Min.) |
|-----------|------|-------|------|----------------|
| CWR6-1R0K | 1.0  | 0.011 | 3.5  | 130            |
|           |      |       |      | 115            |
| CWR6-2R2K | 2.2  | 0.011 | 3.5  | 100            |
|           |      |       |      | 85             |
| CWR6-4R7K | 4.7  | 0.015 | 3.5  | 76             |
|           |      |       |      | 67             |
| CWR6-100K | 10   | 0.023 | 3.5  | 60             |
|           |      |       |      | 50             |
| CWR6-220K | 22   | 0.034 | 3.5  | 46             |
|           |      |       |      | 39             |
| CWR6-470K | 47   | 0.100 | 3.5  | 34             |
|           |      |       |      | 7.0            |
| CWR6-101K | 100  | 0.133 | 3.5  | 3.0            |
|           |      |       |      | 1.6            |
| CWR6-221K | 220  | 0.181 | 1.5  | 1.5            |
|           |      |       |      | 1.0            |
| CWR6-471K | 470  | 0.366 | 0.73 | 0.87           |
|           |      |       |      | 0.87           |
| CWR6-102K | 1000 | 0.544 | 0.14 | 0.66           |

※ Specifications other than the above will be furnished upon request.